



FRENZELIT Graphite sealing sheet NOVAPHIT SSTC



Characteristics

Series: NOVAPHIT

Type: SSTC

Graphite purity: ≥99 %

Ash content %: ≤1 %

Insert material: RVS 316 L (1.4404)

Insert type: Expanded mesh

Number of inserts: 1

Temperature range: -200 / 450 °C

Max. pressure: 250 bar

Characteristics (2)

Suitable for medium: Solvents, Fuels, Chlorine, gaseous (7782-50-5), Low pressure steam, Food & Beverages, Air (compressed air), Natural gas, Weak Acids, Lubricant, Hydrocarbons, Chlorine Water < 5% (7782-50-5), Grease, Refrigerants, Oil, Biodiesel, Weak Alkalis, Cryogenic

Approval according to: Germanischer Lloyd, EC1935/2004, DVGW, FIRE-SAFE ISO 10497, BAM

Thickness mm	Length mm	Width mm	Article
1	1000	1000	11130641
1.5	1000	1000	11013955
2	1500	1500	11013956
2	1000	1000	11295949
3	1500	1500	11258322
3	1000	1000	11013957

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.