



GORE® PTFE sealing sheet GORE GR

For industrial use only.

Not for use in food, drug, cosmetic, or medical device manufacturing, processing, or packaging operations.

Characteristics

- Series: GORE
- Type: GR
- Material structure: Multidirectional expanded PTFE
- Max. temperature: 230 °C
- Minimum temperature: -60 °C
- Max. pressure: 40 bar

- Suitable for medium: Alkalis, Air (compressed air), Weak Alkalis, Weak Acids, Chlorine, gaseous [7782-50-5], Strong Alkalis, Cryogenic, Refrigerants, Solvents, Strong Acids, Chlorine Water < 5% [7782-50-5], Acids
- Approval according to: ABS type approval, Blow out VDI2200, TA-Luft, BAM
- Marking: Printed

Application

- Recommended in: Chemical

Thickness	Length	Width	Article
mm	mm	mm	
0.5	1500	1500	10016821
1.5	1500	1500	10016823
2	1500	1500	10016824
3	1500	1500	10016825
5	1500	1500	11015226
6	1500	1500	10016826

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.