



GARLOCK PTFE sealing sheet GYLON 3504

Characteristics

Series: GYLON
Type: 3504
Material structure: PTFE, modified
Max. temperature: 260 °C
Minimum temperature: -210 °C
Max. pressure: 83 bar

Suitable for medium: Refrigerants, Weak Acids, Alkalis, Potable water, Fuels, Acids, Air (compressed air), Cryogenic, Oil, Food & Beverages, Solvents, Weak Alkalis, Hydrocarbons, Chlorine, gaseous [7782-50-5]

Approval according to: TA-Luft, FDA 21 CFR 177.1550, Belgaqua, BAM, USP Class VI, ABS type approval, Blow out VDI2200, EC1935 (10/2011)

Marking: Printed

Application

- Recommended in: Chemical, Pharma

Thickness	Length	Width	Article
mm	mm	mm	
0.8	750	750	11060314
1.6	1500	1500	10016798
2	1500	1500	10016799
3.2	1500	1500	10016800
4.8	1500	1500	10016801
6.4	1500	1500	11274627

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.