



LEADER PTFE sealing sheet CLIPPERLON 2110

Characteristics

Series: CLIPPERLON

Type: 2110

Material structure: PTFE, modified

Max. temperature: 240 °C

Minimum temperature: -210 °C

Max. pressure: 40 bar

Suitable for medium: Air (compressed air), Low pressure steam, Chlorine Water < 5% (7782-50-5), Acids, Solvents, Potable water, Fuels, Cryogenic, Hydrocarbons, Refrigerants, Weak Alkalis, Chlorine, gaseous (7782-50-5), Alkalis, Weak Acids, Food & Beverages

Approval according to: Blow out VDI2200, EC1935 (10/2011), TA-Luft, FDA 21 CFR 177.1550, WRAS

Marking: Printed

Application

- Recommended in: Chemical, Food & Beverages

Thickness mm	Length mm	Width mm	Article
1	1500	1500	11917132
1.5	1500	1500	11917133
2	1500	1500	11917134
3	1500	1500	11917135

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.