

LEADER Graphite flange gasket EGRAFLEX GHE EN 1514-1 IBC



Characteristics

Series: EGRAFLEX

Type: GHE

Norm: EN 1514-1 IBC

Graphite purity: >98 %

Insert material: RVS 316 L (1.4404)


Insert type: Tanged

Number of inserts: 1

Anti-stick: No

Temperature range: -200 / 450 °C

Max. pressure: 100 bar



Characteristics [2]

Suitable for medium: Weak Alkalis, Refrigerants, Oil, Natural gas, Air (compressed air), Cryogenic, Weak Acids, Low pressure steam, Solvents, Fuels, Grease, Hydrocarbons, Biodiesel, Chlorine, gaseous [7782-50-5], Lubricant, Chlorine Water < 5% [7782-50-5]

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
DN10	PN10/40	46	18	2	10001054
DN15	PN10/40	51	22	2	10001055
DN20	PN10/40	61	27	2	10001056
DN25	PN10/40	71	34	2	10001057
DN32	PN10/40	82	43	2	10001058
DN40	PN10/40	92	49	2	10001059
DN50	PN10/40	107	61	2	10001060
DN65	PN10/40	127	77	2	10001061
DN80	PN10/40	142	89	2	10001062
DN100	PN10/16	162	115	2	10001050
DN100	PN25/40	168	115	2	11045607
DN125	PN10/16	192	141	2	10001051
DN125	PN25/40	194	141	2	11045608
DN150	PN10/16	218	169	2	10001052
DN150	PN25/40	224	169	2	11070684
DN200	PN10/16	273	220	2	10001053
DN200	PN25	284	220	2	11045609
DN200	PN40	290	220	2	11045610
DN250	PN10	328	273	2	10001049
DN250	PN16	329	273	2	11055707
DN250	PN25	340	273	2	11045618
DN250	PN40	352	273	2	11045619
DN300	PN10	378	324	2	11045641
DN300	PN16	384	324	2	11045643
DN300	PN25	400	324	2	11045644
DN300	PN40	417	324	2	11045645
DN350	PN10	438	356	2	11045646
DN350	PN16	444	356	2	11045648
DN350	PN25	457	356	2	11045649
DN350	PN40	474	356	2	11045650
DN400	PN10	489	407	2	11045651
DN400	PN16	495	407	2	11045652
DN400	PN25	514	407	2	11045653

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal diameter	Flange pressure stage	Outer diameter	Inner diameter	Thickness	Article
		mm	mm	mm	
DN400	PN40	546	407	2	11045654
DN500	PN10	594	508	2	11045655
DN500	PN16	617	508	2	11045670
DN500	PN25	624	508	2	11045671
DN500	PN40	628	508	2	11045672
DN600	PN10	695	610	2	11045673
DN600	PN16	734	610	2	11045674
DN600	PN25	731	610	2	11045675
DN600	PN40	747	610	2	11045676

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.