



LEADER PTFE flange gasket CLIPPERLON 2120 EN 1514-1

Characteristics

Series: CLIPPERLON

Type: 2120

Norm: EN 1514-1 IBC

Material structure: PTFE, modified

Marking: Printed

Temperature range: -210 / 240 °C

Max. pressure: 85 bar

Suitable for medium: Refrigerants, Low pressure steam, Solvents, Air [compressed air], Strong Alkalis, Alkalis, Chlorine Water < 5% [7782-50-5], Acids, Hydrocarbons, Cryogenic, Weak Acids, Weak Alkalis, Food & Beverages, Chlorine, gaseous [7782-50-5]

Approval according to: TA-Luft, Blow out VDI2200, EC1935 [10/2011], Pamphlet 95 [CI]

Application

- Recommended in: Chemical, Food & Beverages

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
DN15	PN10/40	51	22	2	11934352
DN20	PN10/40	61	27	2	11934353
DN25	PN10/40	71	34	2	11934354
DN32	PN10/40	82	43	2	11934355
DN40	PN10/40	92	49	2	11934356
DN50	PN10/40	107	61	2	11934357
DN65	PN10/40	127	77	2	11934358
DN80	PN10/40	142	89	2	11934359
DN100	PN10/16	162	115	2	11934348
DN125	PN10/16	192	141	2	11934349
DN150	PN10/16	218	169	2	11934350
DN200	PN10/16	273	220	2	11934351
DN300	PN10	378	324	2	11934360
DN350	PN10	438	356	2	11934361
DN400	PN10	489	407	2	11934362
DN450	PN10	539	458	2	11934363
DN500	PN10	594	508	2	11934364
DN600	PN10	695	610	2	11934365

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.