


LEADER Graphite flange gasket EGRAFLEX SPG ASME B16.21

**Characteristics****Series:** EGRAFLEX**Type:** SPG**Norm:** ASME B16.21**Graphite purity:** 98 %**Insert material:** RVS 316 L [1.4404]**Insert type:** Tanged**Number of inserts:** 1**Anti-stick:** No**Temperature range:** -200 / 450 °C**Max. pressure:** 150 bar**Characteristics [2]**

Suitable for medium: Air [compressed air], Low pressure steam, Grease, Oil, Cryogenic, Biodiesel, Solvents, Lubricant, Weak Acids, Fuels, Weak Alkalis, Natural gas, Chlorine, gaseous [7782-50-5], Chlorine Water < 5% [7782-50-5], Hydrocarbons, Refrigerants

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
1/2"	150lbs	48	21	1.5	11322090
1/2"	300/600lbs	54	21	1.5	11322106
3/4"	150lbs	57	27	1.5	11322091
3/4"	300/600lbs	67	27	1.5	11322107
1"	150lbs	67	33	1.5	11322092
1"	300/600lbs	73	33	1.5	11322108
1.1/4"	150lbs	76	42	1.5	11322269
1.1/2"	150lbs	86	48	1.5	11322270
1.1/2"	300/600lbs	95	48	1.5	11322273
2"	150lbs	105	60	1.5	11322093
2"	300/600lbs	111	60	1.5	11322109
2.1/2"	150lbs	124	73	1.5	11322271
2.1/2"	300/600lbs	130	73	1.5	11322274
3"	150lbs	137	89	1.5	11322094
3"	300/600lbs	149	89	1.5	11322110
4"	150lbs	175	114	1.5	11322095
4"	300lbs	181	114	1.5	11322111
5"	150lbs	197	141	1.5	11322096
5"	300lbs	216	141	1.5	11322112
6"	150lbs	222	168	1.5	11322097
6"	300lbs	251	168	1.5	11322113
8"	150lbs	279	219	1.5	11322098
8"	300lbs	308	219	1.5	11322114
8"	600lbs	321	219	1.5	12255216
10"	150lbs	340	273	1.5	11322099
10"	300lbs	362	273	1.5	11322115
10"	600lbs	400	273	1.5	12255217
12"	150lbs	410	324	1.5	11322100
12"	300lbs	422	324	1.5	11322116
12"	600lbs	457	324	1.5	12255218
14"	150lbs	451	356	1.5	11322101
14"	300lbs	486	356	1.5	11322117
14"	600lbs	492	356	1.5	12255219
16"	150lbs	514	406	1.5	11322102
16"	300lbs	540	406	1.5	11322118
16"	600lbs	565	406	1.5	11353111
18"	150lbs	549	457	1.5	11322103

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal diameter	Flange pressure stage	Outer diameter	Inner diameter	Thickness	Article
		mm	mm	mm	
18"	300lbs	597	457	1.5	11322119
18"	600lbs	613	457	1.5	12255220
20"	150lbs	606	508	1.5	11322104
20"	300lbs	654	508	1.5	11322120
20"	600lbs	683	508	1.5	12255221
24"	150lbs	718	610	1.5	11322105
24"	300lbs	775	610	1.5	11322121
24"	600lbs	791	610	1.5	12255222

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.