



GRUNDFOS Submersible pump Series: DP -Vuilwater pomp - gietijzer - 30 mm vrije doorgang

Characteristics

Series: DP

Pressure rating flange: PN10

Material pump casing: Cast iron

Material quality: EN-JL1030

Insulation class acc. to IEC: F

Maximum flow rate	Nominal volume flow rate	Max. immersion depth	Supply voltage	Length connecting cord	Rotational speed	Nominal current	Connection size	Pump height	Article
l/min	m³/h	m		m	rpm	A		mm	
42480	43	10	3 x 400-415V AC	10	2870	2.8	2" [50]	493	23499034
42480	43	10	3 x 400-415V AC	10	2870	2.8	2" [50]	493	23499032
42480	43	10	3 x 400-415V AC	10	2870	2.8	2" [50]	493	23499033
42840	43	10	1 x 230V AC	10	2870	6.1	2" [50]	493	23499029
42840	43	10	1 x 230V AC	10	2870	6.1	2" [50]	493	23499030
42840	43	10	1 x 230V AC	10	2870	6.1	2" [50]	493	23499031
46080	46	10	3 x 400-415V AC	10	2870	5.8	DN65	592	23499046
46080	46	10	3 x 400-415V AC	10	2870	5.8	DN65	592	23499044
46080	46	10	3 x 400-415V AC	10	2870	5.8	DN65	592	23499045
48960	49	10	3 x 400-415V AC	10	2720	3.8	2" [50]	493	23499036
48960	49	10	3 x 400-415V AC	10	2720	3.8	2" [50]	493	23499037
48960	49	10	3 x 400-415V AC	10	2720	3.8	2" [50]	493	23499035

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.