



Safety clamps, stainless steel, in accordance with EN14420-3 type RK

Application

- for mounting hose barbs with safety collar to rubber hoses
- suitable for all industries
- In combination with the right hose barb a safe connection is achieved
- usable for all couplings with tailpiece to EN 14420-2

Working pressure

25 bar

Material

- clamp shell: stainless steel
- nuts and bolts: steel, galvanized

Standards/Approvals

EN 14420-3

Note

one clamp shell consists of: 2 shells, 4 bolts and 4 nuts

Complete assembly

ERIKS can assemble the desired combination of hose, couplings and clamping shells for you.

Options

also available in aluminium, plastic and brass

Characteristics

Type: Safety clamp

Material: AISI 316

Norm: EN 14420-3

Norm	Clamping range mm	Hose ID x Wall Thickness	Article
	69 / 71	50x10	11938991
EN 14420-3	50 / 52	38x6,5	10016135
EN 14420-3	36 / 39	25x6	10016133
EN 14420-3	30 / 33	19x6	10069724
EN 14420-3	78 / 82	63x8	10069718
EN 14420-3	64 / 67	50x8	10016136
EN 14420-3	114 / 119	100x8	10069719
EN 14420-3	43 / 46	32x6	10016134
EN 14420-3	89 / 93	75x8	10016137
EN 14420-3	22 / 24	13x5	10069720

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.