

Hose coupling, with tri-clamp connection type SHTC



Characteristics

- Type of component:** Hose tail coupling
- Material:** Stainless steel (AISI 316)
- Connection type:** Triclamp
- Hose fitting type:** Triclamp DIN 32676
- Connection termination:** ISO
- Elbow angle [degr.]:** 45 °
- Hose tail execution:** Serrated, with safety collar
- Temperature range [°C]:** -10 / 140 °C

Connection termination size	Hose ID [DN]	Maximum operating pressure bar	Maximum operating pressure psi	Article
				11388936
				11406660
				11406657
25/ 8x1 [6,0]	DN06	25	362	11406644
25/ 13x1,5 [10,0]	DN12	25	362	11376086
64,0/ 53,0x1,5 [50,0]	DN25	16	232	11589558
50,5/ 29,0x1,5 [26,0]	DN25	25	362	11277191
50,5/ 41,0x1,5 [38,0]	DN38	25	362	12144035
64,0/ 53,0x1,5 [50,0]	DN50	16	232	11589559
106,0/ 85,0x2,0 [81,0]	DN75	10	145	11181150
119,0/ 104,0x2,0 [100,0]	DN100	10	145	11480129
25/ 12,7x1,65 [9,4]	DN12	25	362	12491576
64,0/ 50,8x1,65 [47,6]	DN12	16	232	11376085
25/ 19,05x1,65 [15,75]	DN12	25	362	11387234
25/ 12,7x1,65 [9,4]	DN12	25	362	11181082
25/ 12,7x1,65 [9,4]	DN16	25	362	11204081
50,5/ 19,05x1,65 [15,75]	DN19	25	362	11352162
25/ 19,05x1,65 [15,75]	DN19	25	362	12133106
OD 50.5 - ID 10.7 mm	DN19	25	362	11425554
34,0/ 19,05x1,65 [15,75]	DN19	25	362	11181125
25/ 12,7x1,65 [9,4]	DN19	25	362	11181124
50,5/ 25,4x1,65 [22,1]	DN25	25	232	11181129
OD 50.5 - ID 22.6 mm	DN25	25	362	12463461
50,5/ 38,1x1,65 [34,8]	DN38	25	362	11385978
77,0/ 63,5x1,65 [60,2]	DN65	16	232	12658695
50,5/ 25,4x1,25 [22,9]	DN12	25	362	11339214
50,5/ 38,1x1,5 [35,1]	DN19	25	362	11337149
50,5/ 38,1x1,5 [35,1]	DN19	25	362	11339213
50,5/ 38,1x1,5 [35,1]	DN25	25	362	11589561
50,5/ 25,4x1,25 [22,9]	DN25	25	362	11589560
50,5/ 38,1x1,5 [35,1]	DN32	25	362	11456324
64,0/ 50,8x1,5 [47,8]	DN38	16	232	12486548
50,5/ 38,1x1,5 [35,1]	DN38	25	362	11373871
OD 50.5 - ID 35.1 mm	DN19	25	362	11455047
64,0/ 48,3x2,0 [44,3]	DN19	16	232	12369078
50,5/ 26,6x1,6 [23,7]	DN19	25	362	11181126
50,5/ 21,3x1,6 [18,1]	DN19	25	362	11443969
50,5/ 26,6x1,6 [23,7]	DN32	25	362	11181131
64,0/ 48,3x2,0 [44,3]	DN50	16	232	11209033

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Connection termination size	Hose ID (DN)	Maximum operating pressure		Article
		bar	psi	
77,0/ 60,3x2,0 [56,3]	DN50	16	232	11181146
OD 77.0 - ID 63.5 mm	DN65	16	232	11181148
50,5/ 29,0x1,5 [26,0]	DN50	25	363	12944717

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

