



Pipe PVC-U

Industrial, high quality pressure PVC-U pipe in accordance to DIN 8061/ 62

, DIN 19532, "DVGW-Arbeitsblatt" and the technical standard of the Gütegemeinschaft Kunststoffrohre Bonn. The pipe is available delivered in lengths of 5 meters, in a dark gray [RAL 7011] color.

Pressure rating of PN10, PN16 or PN20.

Unplasticised Polyvinyl Chloride [PVC-U] is, amongst others, suitable for chemical installations, drinking water applications and applicable in various installations for the food- and beverage industry.

Solely usable in combination with suitable PVC-U solvent cement and primer, and similar quality pipe or fitting.

Characteristics

Material: PVC-U

Pressure rating product: PN10/16/20

Length: 5 m

Diffusion-tight: No

Minimum medium temperature (continuous): 20 °C

Maximum medium temperature (continuous): 60 °C

Pipe colour: Grey

Outer pipe diameter mm	Wall thickness mm	Pressure rating	Article
8	1	PN20	10048263
10	1.2	PN20	10048264
12	1.4	PN20	10048316
16	1.8	PN20	10048317
20	1.5	PN16	10077692
20	2.3	PN20	10048318
25	2.8	PN20	10048319
32	3.6	PN20	10048320
40	4.5	PN20	10048321
50	5.6	PN20	10048322
63	7	PN20	10048299
75	8.4	PN20	10048300
110	12.3	PN20	11063471
125	9.2	PN16	10048312
140	10.3	PN16	10048323
160	11.8	PN16	10048313
200	9.6	PN10	10048218
225	16.7	PN16	11725762
250	11.9	PN10	10048219

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.