

GF Pipe Series: 480 PP-H

Characteristics

Series: 480

Material: PP-H

Pressure rating product: SDR 17.6

Length: 5 m

Diffusion-tight: No

Minimum medium temperature (continuous): 10 °C

Maximum medium temperature (continuous): 95 °C

Pipe colour: Cream



Outer pipe diameter mm	Wall thickness mm	Pressure rating	Article
16	1.8	SDR 11	10048255
20	1.9	SDR 11	10048155
25	1.8	SDR 17.6	10048254
25	2.3	SDR 11	10048156
32	2.9	SDR 11	10048157
40	2.3	SDR 17.6	10048225
40	3.7	SDR 11	10048158
50	2.9	SDR 17.6	10048229
50	4.6	SDR 11	10048159
75	4.3	SDR 17.6	10048224
75	6.8	SDR 11	10048162
90	5.1	SDR 17.6	10048163
90	8.2	SDR 11	10048164
110	6.3	SDR 17.6	10048165
110	10	SDR 11	10048166
125	7.1	SDR 17.6	10048251
125	11.4	SDR 11	10048256
140	8	SDR 17.6	10048257
140	12.7	SDR 11	10048258
160	9.1	SDR 17.6	10048167
160	14.6	SDR 11	10048259
180	16.4	SDR 11	10048260
200	18.2	SDR 11	10048286
225	12.8	SDR 17.6	11873141
225	20.5	SDR 11	10048287
250	22.7	SDR 11	10048047
280	25.4	SDR 11	10048048
355	32.2	SDR 11	12449918
400	36.3	SDR 11	12449920

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.