



FIP Butterfly valve Series: FKOC PVC-C/PVC-C Handle Wafer type

Characteristics

Series: FKOC

Norm: EN [DIN]

Valve design: Centric

Housing material: PVC-C

Connection: Wafer type

Face to Face norm: Manufacturer standard

Operation: Handle

Disk material: PVC-C

Primary spindle seal material: FPM [FKM]

Nominal inner diameter	Pressure rating	Pressure rating flange	Face to Face length	Material liner	Spindle material	Quality class spindle	Minimum medium temperature [continuous]	Maximum medium temperature [continuous]	Article
			mm				°C	°C	
DN65	PN10	PN10	46	EPDM	Stainless steel	1.4021	0	100	11040761
DN65	PN10	PN10	46	FPM [FKM]	Stainless steel	1.4021	0	100	11040820
DN80	PN10	PN10	49	EPDM	Stainless steel	1.4021	0	100	11040764
DN80	PN10	PN10	49	FPM [FKM]	Stainless steel	1.4021	0	100	11040821
DN100	PN10	PN10	56	EPDM	Stainless steel	1.4021	0	100	11040765
DN100	PN10	PN10	56	FPM [FKM]	Stainless steel	1.4021	0	100	11040824
DN125	PN10	PN10	64	EPDM	Stainless steel	1.4021	0	100	11040766
DN125	PN10	PN10	64	FPM [FKM]	Stainless steel	1.4021	0	100	11040827
DN150	PN10	PN10	70	EPDM	Stainless steel	1.4021	0	100	11040768
DN150	PN10	PN10	70	FPM [FKM]	Stainless steel	1.4021	0	100	11040829
DN200	PN10	PN10	71	EPDM	Stainless steel	1.4021	0	100	11040769
DN200	PN10	PN10	71	FPM [FKM]	Stainless steel	1.4021	0	100	11040850

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.