



CENTER LINE RS Butterfly valve Type: 714 Ductile cast iron/ Stainless steel Pneumatic operated Single acting, spring closing Lug type

Characteristics

Type: 714
Norm: EN (DIN)
Valve design: Centric
Housing material: Ductile cast iron
Material quality: EN-JS1030
Surface protection: Epoxy
Connection: Lug type
Standard connection: EN (DIN)
Face to Face norm: EN 558, Series 20
Operation: Pneumatic operated

Characteristics (2)

Operating principle: Single acting, spring closing
Brand actuator: AMG
Top flange standard: ISO 5211 Direct Mount
Housing lining: Replaceable
Disk material: Stainless steel
Quality class disc: 1.4408
Actuator material: Aluminium

Nominal inner diameter	Pressure rating	Pressure rating flange	Face to Face length	Type coding actuator	Material liner	Minimum medium temperature (continuous)	Maximum medium temperature (continuous)	Article
			mm			°C	°C	
DN50	PN10	PN10/16	43	SAF15	EPDM	-10	120	10056677
DN65	PN10	PN10/16	46	SAF15	EPDM	-10	120	10056678
DN80	PN10	PN10/16	46	SAF20	EPDM	-10	120	10056679
DN100	PN10	PN10/16	52	SAF25	EPDM	-10	120	10056680
DN125	PN10	PN10/16	56	SAF30	EPDM	-10	120	10056681
DN150	PN10	PN10/16	56	SAF33	EPDM	-10	120	10056682
DN200	PN10	PN10	60	SAF33	EPDM	-10	120	10056683
DN250	PN10	PN10	68	SAF35	EPDM	-10	120	10056684
DN300	PN10	PN10	78	SAF40	EPDM	-10	120	10056685

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.