

## SPIRAX SARCO Submersible thermostat fig. 9004 series SA128



### Characteristics

**Series:** SA128

**Type:** 9004

**Model:** Immersion thermostat

**Process connection material:** Brass

**Sensor material:** Brass


**Sensor insert diameter:** 25 mm

**Sensor insert length:** 242 mm

**With pocket tube:** No

### Application

- Control of 2-way and 3-way control valves.



| A   | B   | C   | D  | Weight |
|-----|-----|-----|----|--------|
| mm  | mm  | mm  | mm | [kg]   |
| 275 | 185 | 178 | 25 | 1,8    |

| Adjustment range | Maximum medium temperature<br>(continuous) | Length of capillary | Article  |
|------------------|--------------------------------------------|---------------------|----------|
| °C               | °C                                         | m                   |          |
| 40 / 170         | 190                                        | 2                   | 11814923 |
| -20 / 110        | 165                                        | 2                   | 11814921 |
| 40 / 170         | 190                                        | 4                   | 11814924 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.