



SPIRAX SARCO Thermostatic valve fig.9020 series SB gunmetal

Characteristics

Series: SB

Type: 9020

Housing material: Bronze

Material quality: CC491K (RG5)

Pressure rating: PN25

Material disc: AISI 440B

Spring material: Stainless steel

Maximum medium temperature (continuous): 232 °C

DN ["]	Max. diff. press. [bar]	Kv- value	H mm	L mm	Weight [kg]
1/2	17,2	2,58	101	79	1
3/4	10,3	3,86	101	105	1,3
1	6,8	6,8	101	121	1,5

Design pressure	PN 25
Maximum temperature	260 °C

Connection	Nominal inner diameter	Maximum pressure difference bar	Kvs value	Article
Internal thread (BSPP)	1/2" (15)	17.2	3.86	11814930
Internal thread (BSPP)	3/4" (20)	10.3	2.58	11814931
Internal thread (BSPP)	1" (25)	6.8	6.8	11814929

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.