



Hose Abraflex SL, light PU suction & blower hose

Application

- suction and blower hose for light abrasive solids such as dust, powder and fibers
- industrial vacuum cleaner hose

T

temperature range

- -40 °C to +90 °C
- peaks at +125 °C

Properties

- polyurethane, extruded, with completely embedded steel spiral, thickness polyurethane around 0,4 to 0,75 mm, depending on size
- smooth tube, corrugated cover
- ultralight and flexible, also at low temperatures
- gas and liquid tight
- this hose is compressible

Connections

free of choice or to be mounted directly on pipe

Assembly

FIXXED hose clamps

Internal diameter	Wall thickness	Outer diameter	Maximum operating pressure	Minimum burst pressure	Vacuum-resistance at 20 °C	Minimum bending radius	Roll length	Article
mm	mm	mm	bar	bar	%	mm	m	
51	1.8	63.6	1	3	20	40	20	10069523
76	2.1	84.2	1	3	17	65	20	10069529
80	2.1	94.2	1	3	16	65	20	10015399
102	2.1	106.2	1	3	13	85	15	10015400
127	2.4	131.8	1	3	10	105	15	10015402
152	2.7	157.4	1	3	8	125	15	10015404
228	2.9	233.8	1	3	4	185	10	11215395
254	3.2	260.4	1	3	4	210	10	10069537

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.