



Hose Alpo, polyurethane (PU) vacuum cleaner hose with PVC spiral; according to EC1935/2004 and EU 10/2011



Characteristics

Series: ALPO

Application

- light suction and blower hose for light abrasive solids such as dust, powder and fibres
- industrial vacuum cleaner hose

Technical Information

Temperature range

- -40 °C to +80 °C

Construction

- polyurethane, extruded, with a completely embedded PVC spiral, thickness polyurethane around 0,5 mm
- smooth tube and corrugated cover
- ultralight and flexible

Execution

Connections

- free of choice or to be mounted directly on pipe

Assembly

- FIXED hose clamps

Approval

Approvals/regulations

- EC1935/2004 - EU 10/2011 A,B,C,D1,D2,E

Internal diameter	Wall thickness	Outer diameter	Vacuum-resistance at 20 °C	Minimum bending radius	Roll length	Weight	Article
mm	mm	mm	%	mm	m	kg/m	
19	0.4	24.7	25	25	20	0.02	11194309
20	0.4	25.6	25	25	20	0.02	11194312
25	0.4	30.6	25	30	20	0.03	10015662
32	0.4	37.6	20	35	20	0.05	10015663
35	0.5	62.2	20	45	20	0.06	10015664
38	0.5	44.3	20	50	20	0.05	10015665
40	0.5	46.2	20	60	20	0.06	11194356
45	0.5	51.4	20	65	20	0.1	11194358
51	0.5	57.6	20	70	20	0.11	10015666
55	0.5	62.2	20	75	20	0.12	11194555
60	0.5	67.4	16	80	20	0.13	10015667
63	0.5	71.3	16	80	20	0.18	11194556
70	0.6	78.4	16	95	30	0.34	10015668
76	0.6	84.6	16	100	30	0.36	10015669
80	0.6	89	16	110	30	0.38	11194557
90	0.6	99.2	14	125	30	0.43	11194558
102	0.6	111.6	13	140	30	0.64	10015670
110	0.6	120.2	12	150	30	0.69	11194559
120	0.6	130.8	10	160	30	0.75	11194560
127	0.6	137.8	10	170	30	0.79	11194561
130	0.7	141.4	9	170	20	0.61	11194562
140	0.7	151.4	9	180	20	0.85	11194624
152	0.7	164	8	200	20	0.94	11029303
160	0.7	174.4	7	220	20	0.93	11194625
180	0.7	194.4	4	250	20	1.5	11194627

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Internal diameter	Wall thickness	Outer diameter	Vacuum-resistance at 20 °C	Minimum bending radius	Roll length	Weight	Article
mm	mm	mm	%	mm	m	kg/m	
200	0.7	214.4	4	260	20	1.65	11194628
250	0.8	266	4	300	10	1.36	11194629
300	0.8	316.4	3	350	10	1.62	11194630

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.