




Hose CP 475 PTFE-INOX Food, suction/blow hose up to 250 °C



Application

- suction and blower hose for extremely cold air, hot air and aggressive vapors in among others chemical industry
- suitable for the food industry
- also usable as bellows or expansion joint

Temperature range

- -150 °C to +250 °C
- peaks at +270 °C

Properties

- glass fabric, PTFE impregnated, exterior with clamping profile in stainless steel
- high axial compressibility [4:1]
- very flexible and kink resistant
- non-flammable
- very good chemical resistance
- mechanically strong
- anti-adhesive tube
- UV- and ozone resistant
- abrasion protection via external clamp profile

Approvals/regulations

FDA 21 CFR 177.1550

Connections

free of choice or to be mounted directly on pipe

Assembly

worm drive clamps type Spiralex

Internal diameter	Maximum operating pressure	Vacuum-resistance at 20 °C	Minimum bending radius	Roll length	Article
mm	bar	%	mm	m	
50	0.42	27	18	6	11193685
55	0.4	25	20	6	11193686
60	0.38	22	20	6	11193687
65	0.36	20	22	6	11193688
70	0.34	18	22	6	11193689
75	0.33	16	24	6	11193690
80	0.32	14	24	6	11193691
90	0.29	10	26	6	11193692
100	0.19	8.5	28	6	11193743

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Internal diameter	Maximum operating pressure	Vacuum-resistance at 20 °C	Minimum bending radius	Roll length	Article
mm	bar	%	mm	m	
110	0.18	7	30	3	11193744
120	0.17	6	32	3	11193745
125	0.17	6	34	3	11193746
130	0.16	5	34	3	11193747
140	0.16	4	36	3	11193748
150	0.11	3	38	3	11193749
160	0.1	3	40	3	11193750
170	0.1	3	42	3	11193751
175	0.1	3	44	3	11193752
180	0.09	3	44	3	11193753
225	0.08	2	54	3	11193756
250	0.06	1	58	3	11193757
275	0.06	1	64	3	11193758
300	0.05	1	68	3	11193759
350	0.04	1	78	3	11193760
450	0.03	0.5	98	3	11193762
500	0.02	0.5	108	3	11193763
600	0.02	0.5	128	3	11193764

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.