



Hose CP SILIKON 460, suction & blower hose up to 260 °C

Application

- suction and blower hose for cold and hot air, smoke, fumes and exhaust fumes
- also usable as bellows or expansion joint

Temperature range

- -70 °C to +260 °C
- peaks at +280 °C

Properties

- glass fabric, silicone-impregnated with clamping profile in galvanized steel
- high axial compressibility [4:1]
- extremely flexible and kink resistant
- moderately resistant to oil and petrol vapors
- extremely good chemical resistance
- UV- and ozone resistant
- abrasion protection via external clamp profile
- this hose is flam extinguishing

Approvals/regulations

DIN 4102-B1

Connections

free of choice or to be mounted directly on pipe

Assembly

worm drive clamps type Spiralex

Internal diameter	Wall thickness	Maximum operating pressure	Minimum burst pressure	Vacuum-resistance at 20 °C	Minimum bending radius	Roll length	Article
mm	mm	bar	bar	%	mm	m	
50	6	0.56	1.68	30	18	0	11193571
55	6	0.53	1.59	28	20	0	11193572
60	6	0.5	1.5	25	20	0	11193623
65	6	0.48	1.44	23	22	0	11193624
70	6	0.46	1.38	21	22	0	11193625
75	6	0.44	1.32	18	24	0	11193626
80	6	0.42	1.26	16	24	0	11193627
90	6	0.39	1.17	11	26	0	11193628
100	6	0.26	0.78	10	28	0	11193629
110	6	0.24	0.72	8	30	0	11193630
120	6	0.23	0.69	7	32	0	11193631
125	6	0.22	0.66	7	34	0	11193632
130	6	0.22	0.66	6	34	0	11193633
140	6	0.21	0.63	5	36	0	11193634
150	6	0.14	0.42	4	38	0	11193635
160	6	0.14	0.42	3	40	0	11193636
170	6	0.13	0.39	3	42	0	11193637

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Internal diameter	Wall thickness	Maximum operating pressure	Minimum burst pressure	Vacuum-resistance at 20 °C	Minimum bending radius	Roll length	Article
mm	mm	bar	bar	%	mm	m	
175	6	0.13	0.39	3	44	0	11193638
180	6	0.13	0.39	3	44	0	11193639
200	6	0.12	0.36	2	48	0	11193640
215	6	0.11	0.33	2	52	0	11193641
225	6	0.11	0.33	2	54	0	11193642
250	6	0.08	0.24	2	58	0	11193653
275	6	0.08	0.24	1	64	0	11193654
300	6	0.07	0.21	1	68	0	11193655
350	6	0.05	0.15	1	78	0	11193656
400	6	0.05	0.15	1	88	0	11193657
450	6	0.04	0.12		98	0	11193658
500	6	0.03	0.09		108	0	11193659

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.