



Hose EF-2 SIL, ventilation hose for hot air up to 260 °C, 2-ply silicone glass fibre coated with embedded steel helix

Application

suction and blower hose for hot air, smoke, gases, etc.

Temperature range

-85 °C to +260 °C

Properties

- completely embedded steel spiral between 2 layers fiberglass cloth, silicone impregnated and fiberglass cord
- color red

Connections

free of choice or to be mounted directly on pipe

Assembly

FIXXED hose clamps

Internal diameter	Outer diameter	Maximum operating pressure	Vacuum-resistance at 20 °C	Minimum bending radius	Roll length	Article
mm	mm	bar	%	mm	m	
25	18.5	2.8	71	37	4	10015644
32	22	2.7	65	50	4	10015645
35	26	2.7			4	12614941
38	33	2.7	60	60	4	10015646
40	12	2.7			4	11550687
44	14	2.7			4	12648233
51	110	2.6	52	75	4	10015647
63	48	2.45	47	92	4	10015648
70	68	2.4			4	12340710
76	71	2.3	43	116	4	10015649
83	84	2.15	40	129	4	10015650
95	98	2	36	148	4	11060354
102	20	1.9	35	157	4	10015652
114	16	1.6	27	175	4	10015653
127	20	1.4	24	197	4	10015654
140	11	1.2	18	220	4	10015655
152	42	1.1	16	237	4	10015656
178	48	1	12	270	4	10015657
203	66	0.85	9	330	4	10015658
229	16	0.7	7	399	4	11008765
254	19	0.7	7	399	4	10015659

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.