




ECON® Bimetal thermometer fig. 23000 steel/brass insert

Characteristics

Type: 23000
Accuracy class: Class 1.6 EN 13190
Connection location: Below
Process connection: External thread
With pocket tube: Yes
Cabinet material: Steel, galvanized

Characteristics [2]

Process connection material: Brass
Window material: Glass
Material dial: Aluminium
Maximum operating pressure [Bar]: 25 bar
Level of protection (IP value): IP43



Size table:

Cabinet diameter	ØD	L	b	c	d	e	SW	G
	mm	mm	mm	mm	mm	mm	mm	in
R100	100	63	38	11	12	12	21	1/2"
R63	63	100	36	11	12	12	21	1/2"
R63	63	160	36	11	12	12	21	1/2"
R100	100	100	38	11	12	12	21	1/2"

Measuring range °C	Cabinet diameter mm	Size process connection	Insert length mm	Sensor diameter mm	Diameter pocket tube mm	Ring material	Sensor material	Pocket tube material	Article
-30 / 50	100	1/2" BSPP[G]	63	9	12	Steel chromium-plated	Brass	Brass	11145427
0 / 120	63	1/2" BSPP[G]	100	9	12	Steel chromium-plated	Brass	Brass	10060368
0 / 120	63	1/2" BSPP[G]	160	9	12	Steel chromium-plated	Brass	Brass	10060369
0 / 120	100	1/2" BSPP[G]	63	9	12	Steel chromium-plated	Brass	Brass	10060370
0 / 120	100	1/2" BSPP[G]	100	9	12	Steel chromium-plated	Brass	Brass	11041337

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.