



## Bimetal thermometer fig. 678 stainless steel/stainless steel back connection spring

### Characteristics

**Type:** 678

**Accuracy class:** Class 2 EN 13190

**Connection location:** Back

**Connection:** Spring

**With pocket tube:** No

**Cabinet material:** Stainless steel 304


**Window material:** Glass

**Material dial:** Aluminium

**Level of protection (IP value):** IP43

### Size table:

| Cabinet diameter | ØD | b2 | Weight |
|------------------|----|----|--------|
|                  | mm | mm | kg     |
| R63              | 65 | 13 | 0.5    |



| Measuring range | Cabinet diameter | Ring material       | Process connection material | Weight | Article  |
|-----------------|------------------|---------------------|-----------------------------|--------|----------|
| °C              | mm               |                     |                             | kg     |          |
| 0 / 120         | 63               | Stainless steel 304 | Stainless steel 304         | 0.5    | 11811578 |
| 0 / 160         | 63               | Stainless steel 304 | Stainless steel 304         | 0.5    | 11811577 |
| -30 / 60        | 63               | Stainless steel 304 | Stainless steel 304         | 0.5    | 11811576 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.