



ECON® Bourdon tube pressure gauge Type 1415 bottom connection brass

Characteristics

Type: 1415

Model: Bourdon tube pressure gauge

Blow-out included: Yes

Pressure gauge attachment: Direct

Process connection: External thread

Process connection material: Brass

Window material: Glass

Protection class: IP65

Medium temperature: -20 / 60 °C

Ambient temperature: -20 / 60 °C




Figure	R	a	b	c	c1	c2	c3	D	G				
	mm	mm	mm	mm	mm	mm	mm	mm	[bsp]				
SW	Weight												
mm	[kg]												
1415	100	20	55	6	3	20	19	101	1/2"	87	84	22	0.6

Cabinet diameter mm	Measuring range	Pressure unit	Accuracy class	Cabinet filling fluid	Connection location	Size process connection	Cabinet material	Material dial	Maximum overpressure bar	Article
100	-1 / 0	bar	1.0 %	Glycerin	Below	1/2" BSPP[G]	Stainless steel 304	Aluminium	0	10059443
100	-1 / 3	bar	1.0 %	Glycerin	Below	1/2" BSPP[G]	Stainless steel 304	Aluminium	3.9	10059440
100	-1 / 5	bar	1.0 %	Glycerin	Below	1/2" BSPP[G]	Stainless steel 304	Aluminium	6.5	10059441
100	0 / 1	bar	1.0 %	Glycerin	Below	1/2" BSPP[G]	Stainless steel 304	Aluminium	1300	10059659
100	0 / 100	bar	1.0 %	Glycerin	Below	1/2" BSPP[G]	Stainless steel 304	Aluminium	130	10059538
100	0 / 600	bar	1.0 %	Glycerin	Below	1/2" BSPP[G]	Stainless steel 304	Aluminium	780	10059542
160	0 / 250	bar	1.0 %	Glycerin	Below	1/2" BSPP[G]	Stainless steel 304	Aluminium	325	10059555

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.