



ECON® Bourdon tube pressure gauge Type 1401A rear connection brass

Characteristics

Type: 1401A
Model: Bourdon tube pressure gauge
Blow-out included: No
Pressure gauge attachment: Direct
Process connection: External thread
Process connection material: Brass
Window material: Acrylic
Protection class: IP54
Medium temperature: 0 / 50 °C
Ambient temperature: 0 / 50 °C

Application



- Light industry.
- Pneumatics.
- Installation technique.

Technical Information

- Suitable for gases and liquids that do not affect the brass measuring system.
- Measuring ranges according to EN 837-1.

Options

- Double scale for example in bar/psi.
- Damping screw in connection.
- Dial according to customer specification for example company logo.



Size table:

Cabinet diameter	G	b1	c	c1	RA	D	g	SW
		mm	mm	mm	mm	mm	mm	mm
R40	1/8"	27			10	40	46	14
R50	1/4"	30	5	2	13	50	50	14
R63	1/4"	30	5	2	13	62	52	14

Cabinet diameter mm	Measuring range	Pressure unit	Accuracy class	Cabinet filling fluid	Connection location	Size process connection	Cabinet material	Material dial	Maximum overpressure bar	Article
40	-1 / 0	bar	1.6 %	None	Back centric	1/8" BSPP(G)	Stainless steel 304	Aluminium	0	10059891
40	0 / 2.5	bar	1.6 %	None	Back centric	1/8" BSPP(G)	Stainless steel 304	Aluminium	3	10059769
40	0 / 4	bar	1.6 %	None	Back centric	1/8" BSPP(G)	Stainless steel 304	Aluminium	5	10059633
40	0 / 4	bar	1.6 %	None	Back centric	1/8" NPT	Stainless steel 304	Aluminium	5	10059861
40	0 / 6	bar	1.6 %	None	Back centric	1/8" BSPP(G)	Stainless steel 304	Aluminium	7.8	10059634
40	0 / 6	bar	1.6 %	None	Back centric	1/8" NPT	Stainless steel 304	Aluminium	7.8	10059862
40	0 / 10	bar	2.5 %	None	Back centric	1/8" BSPP(G)	Stainless steel 304	Aluminium	13	11249251
40	0 / 10	bar	1.6 %	None	Back centric	1/8" BSPP(G)	Stainless steel 304	Aluminium	13	10059710
40	0 / 16	bar	1.6 %	None	Back centric	1/8" BSPP(G)	Stainless steel 304	Aluminium	20	10059711

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Cabinet diameter mm	Measuring range	Pressure unit	Accuracy class	Cabinet filling fluid	Connection location	Size process connection	Cabinet material	Material dial	Maximum overpressure bar	Article
40	0 / 25	bar	1.6 %	None	Back centric	1/8" BSPP[G]	Stainless steel 304	Aluminium	32	10059712
50	-1 / 0	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	0	10059894
50	0 / 1	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	1.3	10059635
50	0 / 1.6	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	2	10059770
50	0 / 2.5	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	3	10059771
50	0 / 2.5	bar	1.6 %	None	Back centric	1/4" NPT	Stainless steel 304	Aluminium	3	10059911
50	0 / 4	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	5	10059636
50	0 / 6	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	7.8	10059637
50	0 / 10	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	13	10059713
50	0 / 16	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	20	10059714
50	0 / 25	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	32	10059715
63	-1 / 0	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	0	10059721
63	-1 / 1.5	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	1.9	10059822
63	0 / 0.6	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	0.8	10059912
63	0 / 1	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	1.3	10059638
63	0 / 1.6	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	1.9	10059772
63	0 / 2.5	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	3	10059773
63	0 / 4	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	5	10059639
63	0 / 6	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	7.8	10059640
63	0 / 10	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	13	10059716
63	0 / 10	bar	1.6 %	None	Back centric	1/4" NPT	Stainless steel 304	Aluminium	19	11098391
63	0 / 16	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	20	10059717
63	0 / 25	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	32	10059718
63	0 / 60	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	78	10059719
63	0 / 100	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	130	10059774
63	0 / 160	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	208	10059775
63	0 / 250	bar	1.6 %	None	Back centric	1/4" BSPP[G]	Stainless steel 304	Aluminium	325	10059776

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.