



MOBREY Float switch fig. 8315 aluminiumbronze horizontal square A type flange

Characteristics

Series: S195

Type: 8315

Process connection: Flange

Contact type: 1 x NO en 1 x NC

Contact version: Silver

Switching power: 440V / 5A / 2000VA AC - 240V / 1A
/ 35W DC inductive - 240V / 1A / 35W DC resistive

Housing material: Aluminum bronze

Material wet portion housing: Aluminum bronze

Characteristics [2]

Float material: Stainless steel 316

Material cover: Brass

Material of connection: Aluminum bronze


Cable material: CSP

Cable length: 3 m

Level of protection (IP value): IP68

Ambient temperature: -30 / 70 °C

Explosion-proof: No



Model	Mounting	Size process connection	Max. operating pressure bar	Min. specific density of liquid kg/m ³	Float diameter mm	Adjustable differential gap	Switching differential	Shaft length mm	With sleeve	Article
Float switch	Horizontal and vertical	Square A	18		65	Yes		750	No	11814863
Horizontal float switch	Horizontal	Square A	0	750	65	No	13 mm		Yes	12036186
Horizontal float switch	Horizontal	Square A	18	650	65	No	13 mm		No	11814864
Vertical float switch	Vertical	Square A	18	700	129	Yes		1500	No	12036185

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.