



Flange coupling DELTA KU 3311 for DELTA hoses

Characteristics

Type: 3311

Type of component: Hose tail coupling

Material: Aluminium

Connection type: Flange

Hose fitting type: Fixed flange

Connection termination: EN1092 PN10

Elbow angle [degr.]: 0 °

Temperature range [°C]: -20 / 95 °C

Application

- Former type: SIGMA® KU 3311 for the purpose of DELTA hoses
- coupling consisting of two half-sells with integral half-flange

Construction

Material

- aluminum

Options

Additional information

- delivery including nuts and bolts to connect the two coupling halves together
- delivery excluding seal, these are separately available [see DELTA DI 3312]

Complete assembly

- clear assembly instruction are available
- ERIKS can assemble the DELTA hoses equipped with the DELTA hoses.
- special seals are available

Connection termination size	Hose ID [DN]	Maximum operating pressure		Article
		bar	psi	
DN50	DN50	10	145	11092565
DN65	DN63	10	145	11122474
DN80	DN75	10	145	11097344
DN100	DN100	10	145	11087354
DN125	DN110	10	145	11122476
DN125	DN125	10	145	11087355
DN150	DN150	10	145	11122477
DN200	DN200	10	145	11122478

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.