ERIFLON Hose Eriflon PTFE thin walled



Application

- Suitable for use as a delivery hose for conveying a wide range of chemicals and products for the foodstuff and pharmaceutical industries.
- Also suitable for use as an air hose in aggressive environmental conditions.
- Can also be used as an insulation sleeve for electrical applications.
- Recommended in: Pharma

Technical Information

Temperature range

• -70 °C to +260 °C in a depressurised and unloaded state

Construction

Colour

- The Eriflon PTFE tube is supplied in natural milkwhite as standard.
- More colours are available on request, including an antistatic design in black.

Execution

Dimensions

 Various dimensions, such as imperial dimensions and flexible wall thicknesses, are available on request.

Internal diameter	Outer diameter	Maximum operating pressure	Roller length	Maximum operating pressure	Article
mm	mm	bar	m	MPa	
1	3	60		60	10014661
2	4	30	100	30	10014662
3.15	6.35	17	25	17	10014674
3	5	20	50	20	10014663
4	6	30	50	30	10014664
5	7	10	50	10	10014665
6	8	10	100	10	10014666
8	10	5	100	5	10014667
10.7	12.7	5	50	5	10014672
10	12	5	100	5	10014668
12	14	5	100	5	10014657
14	16	5		5	10014669
16	18	3	50	3	10014670
20	22	3	50	3	10014671

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

ERIKS

PR_EC011297_0014_EN_21.05.2024