



Rubber hose Superflex, SBR water suction hose

Application

- light suction hose for water, waste water etc.
- the most flexible suction hose, the grooved cover prevents kinking of the hose

Technical Information

Temperature range

- -30 °C to +60 °C

Burst pressure

- minimum 5 bar
- safety factor 2,5:1

Construction

Tube

- black SBR rubber
- smooth

Reinforcement

- spiral-plied textile fabrics, steel spiral

Cover

- black SBR rubber
- grooved with spiral free cuffs

Execution

Connections

- free of choice

Assembly

- FIXXED hose clamps or Band-it

Options

Comments

- This hose can only be supplied in standard lengths, provide of spiral free cuffs.

Internal diameter	Wall thickness	Outer diameter	Maximum operating pressure	Minimum burst pressure	Vacuum-resistance at 20 °C	Minimum bending radius	Roll length	Article
mm	mm	mm	bar	bar	%	mm	m	
50	6	62	2	6	70	300	6	11381843
75	6	87	2	6	70	300	6	10015863
102	6.5	115	2	6	70	400	3	10015859
102	6.5	115	2	6	70	400	6	10015864
102	6.5	115	2	6	70	400	4	10015860

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.