



Rubber hose Trix-Rotstrahl, EPDM water discharge hose

Characteristics

Series: Trix-Rotstrahl

Application

- universal, robust industrial hose for cold and warm water
- also used often as deck washing hose in places where a wear resistant cover is required

Technical Information

Temperature range

- -40 °C to +100 °C

Burst pressure

- 3 x working pressure
- safety factor 3:1

Construction

Tube

- black EPDM rubber

Reinforcement

- spiral-ply synthetic fabrics with extremely high tensile strength

Cover

- EPDM rubber, black with red longitudinal stripes

Execution

Branding

- "TRIX ROTSTRAHL DN... PN ... BAR / ... PSI Made in Germany"

Connections

- free of choice

Assembly

- FIXED hose clamps or ferrules

Options

Complete assembly

- ERIKS can assemble the Trix-Rotstrahl with your required couplings.

Internal diameter	Wall thickness	Outer diameter	Maximum operating pressure	Minimum burst pressure	Minimum bending radius	Roll length	Weight	Article
mm	mm	mm	bar	bar	mm	m	kg/m	
13	3.3	19.6	20	60	50	40	0.25	10014714
16	3.5	23	20	60	60	40	0.33	10014715
19	4	27	20	60	65	40	0.44	10014716
22	4.5	31	20	60	70	40	0.52	10014717
25	4.5	34	20	60	110	40	0.58	10014718
32	5.5	43	15	45	170	40	0.89	10014719
38	6	50	15	45	200	40	1.1	10014720
50	7	64	10	30	300	40	1.57	10014721

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.