# GOODALL Rubber hose Titon Black, EPDM air and water discharge hose 20 bar, completely electrically conductive $\Omega/T$



Ω

## **Characteristics**

Series: Titon Type: Black

## Application

- premium multi-purpose hose for compressed air, water and aqueous solutions
- the hose is especially suitable as an air hose
- easy to handle, kink resistant, crush proof and flexible, even at low temperatures
- suitable as water or air hose for chemical, petrochemical and other industrial markets, but also for construction and agriculture applications
- completely electrically conductive
- Recommended in: Chemical

# **Technical Information**

Temperature range depending on medium • -40°F/-40°C tot 248°F/120°C

- **Burst pressure**
- safety factor 4:1

## Construction

#### Tube

- black EPDM rubber
- smooth and seamlessly extruded
- electrically conductive R <  $10^6 \Omega$

## Reinforcement

- 4 spiral polyester layers
- high tensile strength

#### Cover

- black EPDM rubber
- smooth, abrasion resistant
- seamlessly extruded
- resistant to heat, extreme weather and ozone
- electrically conductive R <  $10^6 \Omega$

# Execution

## Branding

 $\bullet$  GOODALL TITON 300PSI/20BAR WP SIZE 248°F/120° C  $\Omega$ 

## Connections

- free of choice
- Assembly
- FIXXED hose clamps or ferrules

# Options

#### **Complete assembly**

• ERIKS can assemble the Titon Black with your required couplings.

## Options

- hydrostatic test report
- excellent laser engraving on marking ferrule

Internal diameter	Wall thickness	Outer diameter	Maximum operating pressure	Minimum burst pressure	Minimum bending radius	Roll length	Weight	Article
mm	mm	mm	bar	bar	mm	m	kg/m	
6	3.4	12.8	20	80	38	100	0.13	12676842
8	3.9	15.8	20	80	51	100	0.19	12676853
13	4.6	22.2	20	80	76	100	0.36	12676855
16	4.7	25.4	20	80	95	100	0.46	12676856
19	5.1	29.2	20	80	114	60	0.6	13195119
25	5.7	36.4	20	80	178	60	0.73	13244818
32	6.2	44.4	15	60	222	60	1.18	13244819
38	6.4	50.8	15	60	267	60	1.34	13244820
	3.8	17.6	20	80	57	60		13244815

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1