

GOODALL Rubber hose Multi Red, EPDM air and water pressure hose 20 bar; Ω



Application

- flexible, universal, multipurpose hose for air and water
- this hose retains its flexibility at lower temperatures
- very suitable for pneumatic tooling

Technical Information

Temperature range

- -30 °C to +90 °C

Burst pressure

- minimum 60 bar
- safety factor 3:1

Construction

Tube

- black EPDM rubber
- antistatic

Reinforcement

- braided textile fabrics

Cover

- red EPDM rubber
- smooth
- wear resistant
- ozone and weather resistant

Execution

Branding

- imprinted text: "GOODALL MULTI 20bar WP SIZE Max.70°C Ω [15400]"

Connections

- free of choice

Assembly

- FIXXED hose clamps, Band-it or ferrules

Options

Complete assembly

- ERIKS can assemble the Multi Red with your required couplings.

Options

- hydrostatic test report
- excellent laser engraving on marking ferrule

Internal diameter	Wall thickness	Outer diameter	Maximum operating pressure	Minimum burst pressure	Minimum bending radius	Roll length	Weight	Article
mm	mm	mm	bar	bar	mm	m	kg/m	
19	5	29	20	60	152	120	0.5	10015894

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.