

## GOODALL Rubber hose Multi Blue, EPDM air and water pressure hose 20 bar; Ω



### Application

- flexible, universal, multipurpose hose for air and water
- this hose retains its flexibility at lower temperatures
- very suitable for pneumatic tooling

### Technical Information

#### Temperature range

- -30 °C to +70 °C

#### Burst pressure

- minimum 60 bar
- safety factor 3:1

### Construction

#### Tube

- black EPDM rubber
- antistatic

#### Reinforcement

- braided textile fabrics

#### Cover

- blue EPDM rubber
- smooth
- wear resistant
- ozone and weather resistant

### Execution

#### Branding

- imprinted text: "GOODALL MULTI 20bar WP SIZE Max.70°C Ω [15400]"

#### Connections

- free of choice

#### Assembly

- FIXXED hose clamps, Band-it or ferrules

### Options

#### Complete assembly

- ERIKS can assemble the Multi Blue with your required couplings.

#### Options

- hydrostatic test report
- excellent laser engraving on marking ferrule

| Internal diameter | Wall thickness | Outer diameter | Maximum operating pressure | Minimum burst pressure | Minimum bending radius | Roll length | Weight | Article  |
|-------------------|----------------|----------------|----------------------------|------------------------|------------------------|-------------|--------|----------|
| mm                | mm             | mm             | bar                        | bar                    | mm                     | m           | kg/m   |          |
| 13                | 5              | 23             | 20                         | 60                     | 100                    | 120         | 0.38   | 13219077 |
| 16                | 5              | 26             | 20                         | 60                     | 125                    | 120         | 0.44   | 12099328 |
| 19                | 5              | 29             | 20                         | 60                     | 155                    | 120         | 0.51   | 10015884 |
| 25                | 6              | 37             | 20                         | 60                     | 205                    | 120         | 0.79   | 13219075 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.