



GRUNDFOS Submersible pump Series: SE - Vuilwater pomp

Characteristics

Series: SE

Connection: Flange

Pressure rating flange: PN10

Material pump casing: Cast iron

Material quality: EN-JL1040

Insulation class acc. to IEC: F

Maximum flow rate	Nominal volume flow rate	Max. immersion depth	Supply voltage	Length connecting cord	Rotational speed	Nominal current	Connection size	Pump height	Article
l/min	m³/h	m		m	rpm	A		mm	
69840	70	20	3 x 380-415V AC	10	2910	6.8	DN65	753	23498321
69840	70	20	3 x 380-415V AC	10	2910	6.8	DN80	760	23498413
69840	70	20	3 x 380-415V AC	10	2925	8.7	DN80	838	23498417
74880	75	20	3 x 380-415V AC	10	2895	5.1	DN65	753	23498317
74880	75	20	3 x 380-415V AC	10	2895	5.1	DN80	760	23498409
87840	88	20	3 x 380-415V AC	10	2925	8.7	DN65	831	23498325
123120	123	20	3 x 380-415V AC	10	1435	4.2	DN80	776	23498329
128160	128	20	3 x 380-415V AC	10	1435	4.2	DN100	788	23498421
132840	133	20	3 x 380-415V AC	10	1445	6	DN80	776	23498333
138960	139	20	3 x 380-415V AC	10	1445	6	DN100	788	23498425
151920	152	20	3 x 380-415V AC	10	1455	7.8	DN80	878	23498337
151920	177	20	3 x 380-415V AC	10	1460	10	DN80	878	23498341
158040	158	20	3 x 380-415V AC	10	1455	7.8	DN100	878	23498429
183960	184	20	3 x 380-415V AC	10	1460	10	DN100	878	23498433
228960	229	20	3 x 380-415V AC	10	1460	10	DN100	885	23498353
231840	232	20	3 x 380-415V AC	10	1460	10	DN150	900	23498445

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.