



JC Ball valve Series: 401LICG Type: 3324 Steel Fire safe Internal thread (NPT) Class 800

Characteristics

Series: 401LICG

Type: 3324

Norm: ASME

Construction type: 2-way

Housing construction: 1-part

Housing material: Steel

Material quality: ASTM A350 LF2

Surface protection: Coated

Connection: Internal thread (NPT)

Primary spindle seal material: RPTFE

Secondary spindle seal material: FPM (FKM)

Tertiary spindle seal material: Graphite

Body seal: PTFE

Minimum medium temperature (continuous): -46 °C

Maximum medium temperature (continuous): 260 °C

Fire safe: Yes

Application

- Recommended in: Chemical

Nominal inner diameter	Standard thread connection	Pressure rating	Face to Face norm	Manual operation	Bore	Material ball	Seat material	Spindle material	Actuator material	Article
1/2" [15]	ASME B1.20.1	Class 800	Manufacturer standard	Handle	Full bore	ASTM A351 CF8M	RPTFE	1.4006	Steel, nickel plated	11612331
3/4" [20]	ASME B1.20.1	Class 800	Manufacturer standard	Handle	Full bore	ASTM A351 CF8M	RPTFE	1.4006	Steel, nickel plated	11612333
1" [25]	ASME B1.20.1	Class 800	Manufacturer standard	Handle	Full bore	ASTM A351 CF8M	RPTFE	1.4006	Steel, nickel plated	11612335
1.1/2" [40]	ASME B1.20.1	Class 800	Manufacturer standard	Handle	Full bore	ASTM A351 CF8M	RPTFE	1.4006	Ductile cast iron	11612334
2" [50]	ASME B1.20.1	Class 800	Manufacturer standard	Handle	Full bore	ASTM A351 CF8M	RPTFE	1.4006	Ductile cast iron	11609859

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.