



MECAFRANCE Ball valve Type: 3460 Stainless steel Pneumatic operated Double acting Butt weld EN ISO 1127-1 PN50 to PN100

Characteristics

Type: 3460

Norm: EN (DIN)

Construction type: 2-way

Housing construction: 3-part

Housing material: Stainless steel

Material quality: 1.4408

Connection: Butt weld

Standard welding connection: EN ISO 1127-1

Actuator: Pneumatic operated

Operating principle: Double acting


Top flange standard: ISO 5211

Tertiary spindle seal material: RPTFE

Actuator material: Aluminum anodized

Application

- Recommended in: Food & Beverages, Food primary processes (contact with food)



Nominal inner diameter	Pressure rating	Face to Face norm	Type coding actuator	Brand actuator	Bore	Material ball	Seat material	Spindle material	Primary spindle seal material	Article
1/2" [15]	PN100	Manufacturer standard	SAD05	AMG	Full bore	Stainless steel	PTFE	Stainless steel	RPTFE	10054716
3/4" [20]	PN100	Manufacturer standard	SAD05	AMG	Full bore	Stainless steel	PTFE	Stainless steel	RPTFE	10054717
1" [25]	PN100	Manufacturer standard	SAD10	AMG	Full bore	Stainless steel	PTFE	Stainless steel	RPTFE	10054719
1.1/4" [32]	PN63	Manufacturer standard	SAD10	AMG	Full bore	Stainless steel	PTFE	Stainless steel	RPTFE	10054720
1.1/2" [40]	PN63	Manufacturer standard	SAD10	AMG	Full bore	Stainless steel	PTFE	Stainless steel	RPTFE	10054722
2" [50]	PN50	Manufacturer standard	SAD15	AMG	Full bore	Stainless steel	PTFE	Stainless steel	RPTFE	10054721

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.