

# JC Ball valve Series: 516AIT/540AIT Type: 3191 Steel Fire safe Pneumatic operated Single acting, spring closing Flange PN16/40

Mounted, pneumatically operated 2-way ball valve, consisting of: Two-piece JC ball valve (type: 3191) and single-acting pneumatic AMG actuator (type: 7971).

The pneumatically operated 2-way ball valve is configured on the basis of the following setup: Pneumatic pilot pressure at 6 bar, medium is water, medium temperature is max. 100°C, ball valve is actuated at least a few times daily, actuator structure according to Eriks standard.

#### **Characteristics**

Series: 516AIT/540AIT

**Type:** 3191 Norm: EN (DIN)

Construction type: 2-way Housing construction: 2-part Housing material: Steel Material quality: 1.0619 **Connection:** Flange

Actuator: Pneumatic operated

Operating principle: Single acting, spring closing

Top flange standard: ISO 5211

Secondary spindle seal material: FPM (FKM) Tertiary spindle seal material: Graphite Body seal: SWG 316L/PTFE/Graphite Actuator material: Aluminum anodized

Minimum medium temperature (continuous): -20 °C

Fire safe: Yes

# **Application**

- Heavy-duty industrial applications up to 16 or 40 bar.
- Recommended in: Chemical

### **Technical Information**

- Flanged connection in accordance with EN 1092-1.
- Floating ball.
- Pressure rating PN16 or PN40.
- With top-flange in accordance with ISO 5211.
- Media temperature: -29/+230°C.
- The actuator can be fitted with a multifunctional position indicator suitable for mechanical limit switches or double proximity sensors.
- Air supply and upper flanged connection of actuator in accordance with NAMUR VDI/VDE 3845.

## **Construction**

- Two-piece housing construction.
- Design in accordance with EN 12516 and EN 1983.
- Full flow capacity.
- Equipped with antistatic design between ball and
- According to NACE MR0175/ISO 15156 & AMP, NACE MR0103/ISO 17945.
- Construction length in accordance with EN 558, series 27.

### **Approval**

- Fire-safe certified in accordance with ISO 10497, API 6FA and API 607.
- Fugitive emissions certified according to TA Luft.
- Fugitive emissions certified in accordance with ISO 15848-1 (VDI 2440), class B, and optionally according to ISO 15848-1, class A, with double spindle seal.
- Safety class of ball valve in accordance with IEC 61508 SIL 3.
- Safety class of actuator in accordance with IEC 61508 SIL 2 (SIL 3 for redundant configuration).

### **Options**

- Equipped with a pneumatic and double-acting actuator.
- Position feedback.
- Pressure-relief seats or a pressure-relief hole in the
- Dead space free seats.
- Stainless steel extended spindle.
- Other seat materials.

Nominal inner diameter	Pressure rating	Face to Face norm	Type coding actuator	Brand actuator	Bore	Material ball	Seat material	Spindle material	Primary spindle seal material	Article
DN15	PN40	EN 558, Series	SAF10	AMG	Full bore	1.4401	PTFE	1.4401	RPTFE	10054604

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

EC011343\_0139\_EN\_06.05.2024

# Ball Valves | Automated ball valves with flange connection

Nominal inner diameter	Pressure rating	Face to Face norm	Type coding actuator	Brand actuator	Bore	Material ball	Seat material	Spindle material	Primary spindle seal material	Article
DN15	PN40	EN 558, Series 27	SAF15	AMG	Full bore	1.4401	PTFE	1.4401	RPTFE	11087153
DN20	PN40	EN 558, Series 27	SAF15	AMG	Full bore	1.4401	PTFE	1.4401	RPTFE	10054605
DN25	PN40	EN 558, Series 27	SAF15	AMG	Full bore	1.4401	PTFE	1.4401	RPTFE	10054606
DN25	PN40	EN 558, Series 27	SAF20	AMG	Full bore	1.4401	PTFE	1.4401	RPTFE	11038019
DN32	PN40	EN 558, Series 27	SAF15	AMG	Full bore	1.4408	PTFE	1.4401	RPTFE	10054607
DN40	PN40	EN 558, Series 27	SAF20	AMG	Full bore	1.4408	PTFE	1.4401	RPTFE	10054608
DN50	PN40	EN 558, Series 27	SAF25	AMG	Full bore	1.4408	PTFE	1.4401	RPTFE	10054609
DN65	PN16	EN 558, Series 27	SAF30	AMG	Full bore	1.4408	PTFE	1.4401	RPTFE	10054615
DN80	PN40	EN 558, Series 27	SAF30	AMG	Full bore	1.4408	PTFE	1.4401	RPTFE	10054621
DN100	PN16	EN 558, Series 27	SAF35	AMG	Full bore	1.4408	PTFE	1.4401	RPTFE	11386114
DN100	PN16	EN 558, Series 27	SAF33	AMG	Full bore	1.4408	PTFE	1.4401	RPTFE	10054616
DN125	PN16	EN 558, Series 27	SAF35	AMG	Full bore	1.4408	PTFE	1.4401	RPTFE	10054617
DN150	PN16	EN 558, Series 27	SAF40	AMG	Full bore	1.4408	PTFE	1.4401	RPTFE	10054618
DN200	PN16	EN 558, Series 27	SAF42	AMG	Full bore	1.4408	PTFE	1.4401	RPTFE	10054619

e o r e advice.
Page 2/2
PR\_ECO11343\_0139\_EN\_06.05.2024 Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.