



FIP Ball valve Series: VKDIC PVC-C Pneumatic operated Double acting Glued sleeve PN16

Characteristics

Series: VKDIC

Construction type: 2-way

Housing construction: 3-part

Housing material: PVC-C

Connection: Glued sleeve

Actuator: Pneumatic operated

Operating principle: Double acting

Seat material: PTFE

Actuator material: Aluminium

Nominal inner diameter	External tube diameter of connection mm	Pressure rating	Face to Face norm	Type coding actuator	Brand actuator	Material ball	Primary spindle seal material	Secondary spindle seal material	Body seal	Article
DN15	20	PN16	Manufacturer standard	DA20	ECON	PVC-C	EPDM	EPDM	EPDM	11347747
DN15	20	PN16	Manufacturer standard	DA20	ECON	PVC-C	FPM (FKM)	FPM (FKM)	FPM (FKM)	11347756
DN20	25	PN16	Manufacturer standard	DA20	ECON	PVC-C	EPDM	EPDM	EPDM	11347748
DN20	25	PN16	Manufacturer standard	DA20	ECON	PVC-C	FPM (FKM)	FPM (FKM)	FPM (FKM)	11347757
DN25	32	PN16	Manufacturer standard	DA20	ECON	PVC-C	EPDM	EPDM	EPDM	11347749
DN25	32	PN16	Manufacturer standard	DA20	ECON	PVC-C	FPM (FKM)	FPM (FKM)	FPM (FKM)	11347758
DN32	40	PN16	Manufacturer standard	DA80	ECON	PVC-C	EPDM	EPDM	EPDM	11347750
DN32	40	PN16	Manufacturer standard	DA80	ECON	PVC-C	FPM (FKM)	FPM (FKM)	FPM (FKM)	11347759
DN40	50	PN16	Manufacturer standard	DA80	ECON	PVC-C	EPDM	EPDM	EPDM	11347751
DN40	50	PN16	Manufacturer standard	DA80	ECON	PVC-C	FPM (FKM)	FPM (FKM)	FPM (FKM)	11347760
DN50	63	PN16	Manufacturer standard	DA80	ECON	PVC-C	EPDM	EPDM	EPDM	11347752
DN50	63	PN16	Manufacturer standard	DA80	ECON	PVC-C	FPM (FKM)	FPM (FKM)	FPM (FKM)	11347761

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.