



FIP Ball valve Series: VKDIC PVC-C Electric operated Glued sleeve PN16

Characteristics

Series: VKDIC

Construction type: 2-way

Housing construction: 3-part

Housing material: PVC-C

Connection: Glued sleeve

Actuator: Electric operated

Material ball: PVC-C

Seat material: PTFE

Actuator material: Polyamide

Nominal inner diameter	External tube diameter of connection mm	Pressure rating	Face to Face norm	Type coding actuator	Brand actuator	Supply voltage	Primary spindle seal material	Secondary spindle seal material	Body seal	Article
DN40	50	PN16	Manufacturer standard	ER20	ECON	230V AC	EPDM	EPDM	EPDM	11347769
DN40	50	PN16	Manufacturer standard	ER20	ECON	24V AC/DC	EPDM	EPDM	EPDM	11347787
DN40	50	PN16	Manufacturer standard	ER20	ECON	24V AC/DC	FPM (FKM)	FPM (FKM)	FPM (FKM)	11347796
DN40	50	PN16	Manufacturer standard	ER20	ECON	230V AC	FPM (FKM)	FPM (FKM)	FPM (FKM)	11347778

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.