

DURAPIPE Ball valve Series: VKD ABS Glued sleeve PN16



Characteristics

Series: VKD
Construction type: 2-way
Housing construction: 3-part
Housing material: ABS
Connection: Glued sleeve
Primary spindle seal material: EPDM
Secondary spindle seal material: EPDM

Characteristics (2)

Body seal: EPDM
Minimum medium temperature (continuous): -40 °C
Maximum medium temperature (continuous): 70 °C
With drain: No



Nominal inner diameter	External tube diameter of connection mm	Pressure rating	Face to Face norm	Manual operation	Bore	With locking device	Material ball	Seat material	Spindle material	Article
DN10	16	PN16	Manufacturer standard	Handle	Full bore		ABS	PTFE	ABS	10055106
DN15	20	PN16	Manufacturer standard	Handle	Full bore		ABS	PTFE	ABS	10055107
DN20	25	PN16	Manufacturer standard	Handle	Full bore		ABS	PTFE	ABS	10055108
DN25	32	PN16	Manufacturer standard	Handle	Full bore		ABS	PTFE	ABS	10055109
DN32	40	PN16	Manufacturer standard	Handle	Full bore		ABS	PTFE	ABS	10055110
DN40	50	PN16	Manufacturer standard	Handle	Full bore		ABS	PTFE	ABS	10055111
DN50	63	PN16	Manufacturer standard	Handle	Full bore		ABS	PTFE	ABS	10055112
DN65	75	PN16	Manufacturer standard	Handle	Full bore		ABS	PTFE	ABS	10055113
DN80	90	PN16	Manufacturer standard	Handle	Full bore		ABS	PTFE	ABS	10055114
DN100	110	PN16	Manufacturer standard	Handle	Full bore		ABS	PTFE	ABS	10055115

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.