



GF Ball valve Series: 546 PVDF Plastic welded end PN16

Characteristics

Series: 546

Construction type: 2-way

Housing construction: 3-part

Housing material: PVDF

Connection: Plastic welded end

Nominal inner diameter	External tube diameter of connection mm	Pressure rating	Face to Face norm	Manual operation	Material ball	Seat material	Primary spindle seal material	Secondary spindle seal material	Body seal	Article
DN25	32	PN16	Manufacturer standard	Handle	PVDF	PTFE	FPM (FKM)	FPM (FKM)	FPM (FKM)	11461414
DN32	40	PN16	Manufacturer standard	Handle	PVDF	PTFE	FPM (FKM)	FPM (FKM)	FPM (FKM)	11933220
DN40	50	PN16	Manufacturer standard	Handle	PVDF	PTFE	FPM (FKM)	FPM (FKM)	FPM (FKM)	11604280
DN50	63	PN16	Manufacturer standard	Handle	PVDF	PTFE	FPM (FKM)	FPM (FKM)	FPM (FKM)	11518186

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.