



FIP Ball valve Series: VKDIF PVDF Plastic welded sleeve PN16

Characteristics

Series: VKDIF
Construction type: 2-way
Housing construction: 3-part
Housing material: PVDF
Connection: Plastic welded sleeve
Primary spindle seal material: FPM (FKM)
Secondary spindle seal material: FPM (FKM)

Characteristics [2]

Body seal: FPM (FKM)
Minimum medium temperature (continuous): -20 °C
Maximum medium temperature (continuous): 140 °C
With drain: No

Nominal inner diameter	External tube diameter of connection mm	Pressure rating	Face to Face norm	Manual operation	Bore	With locking device	Material ball	Seat material	Spindle material	Article
DN10	16	PN16	Manufacturer standard	Handle	Full bore		PVDF	PTFE	PVDF	10055371
DN15	20	PN16	Manufacturer standard	Handle	Full bore		PVDF	PTFE	PVDF	10055372
DN20	25	PN16	Manufacturer standard	Handle	Full bore		PVDF	PTFE	PVDF	10055373
DN25	32	PN16	Manufacturer standard	Handle	Full bore		PVDF	PTFE	PVDF	10055374
DN32	40	PN16	Manufacturer standard	Handle	Full bore		PVDF	PTFE	PVDF	10055375
DN40	50	PN16	Manufacturer standard	Handle	Full bore		PVDF	PTFE	PVDF	10055376
DN50	63	PN16	Manufacturer standard	Handle	Full bore		PVDF	PTFE	PVDF	10055377
DN65	75	PN16	Manufacturer standard	Handle	Full bore		PVDF	PTFE	PVDF	10055378
DN80	90	PN16	Manufacturer standard	Handle	Full bore		PVDF	PTFE	PVDF	10055379

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.