



ECON® Ball valve Type: 7444ED Stainless steel Pneumatic operated Double acting Internal thread (BSPP) 1000 PSI WOG



Mounted, pneumatically operated 2-way ball valve, consisting of: Three-piece Econ® ball valve [type: 7444] and double-acting pneumatic Econ® actuator [type: 7902].

The pneumatically operated 2-way ball valve is configured according to the following basic principles: Pneumatic pilot pressure at 6 bar, medium is water, medium temperature is max. 100°C, ball valve is actuated at least a few times daily, actuator structure according to Eriks standard.

Characteristics

Type: 7444ED
Norm: EN (DIN)
Construction type: 2-way
Housing construction: 3-part
Housing material: Stainless steel
Material quality: 1.4408
Connection: Internal thread (BSPP)
Actuator: Pneumatic operated
Operating principle: Double acting
Top flange standard: ISO 5211 Direct Mount
Primary spindle seal material: PTFE
Secondary spindle seal material: FPM (FKM)
Tertiary spindle seal material: PTFE
Body seal: PTFE
Actuator material: Aluminium
Minimum medium temperature (continuous): -29 °C
Maximum medium temperature (continuous): 205 °C

Application

- Compressed air, central heating systems, water, fuel and slightly corrosive systems up to a maximum of 68 bar.
- Recommended in: Food & Beverages

Technical Information

- Connection according to ISO 228-1 BSPP.
- Pressure class 1000 PSI WOG
- In sizes 0.25-4 inches.
- Actuator with multifunctional position indicator, suitable for mechanical limit switches or double proximity sensors.
- Air supply and upper flanged connection of drive in accordance with NAMUR VDI/VDE 3845.

Construction

- Three-piece housing construction.
- Design of the ball valve as per MSS SP-110
- Full bore.
- Equipped with anti-static design between ball, spindle and housing.

Approval


- TA Luft certified in accordance with VDI 2440, section 3.3.1.3.
- Declaration of conformity according to EC 1935/2004.

Options

- With single acting pneumatic drive, type 7444ES
- End of service life signalling through switch box or double sensor, type 79650 to 79659
- Positioner, type 3304
- Namur control valve, type 33580
- Stainless-steel extended spindle for insulation [type 8007]
- Connection in NPT according to ASME B1.20.1.

Ball Valves | Automated ball valves with threaded connection

Size table:



DN	d mm	L mm	H mm	B mm	Weight kg
1/4" [8]	10.6	75	138	72.5	2
3/8" [10]	12.7	75	138	72.5	2
1/2" [15]	15	75	138	72.5	2.1
3/4" [20]	20	80	145	72.5	2.3
1" [25]	25	90	155	72.5	2.8
1.1/4" [32]	32	110	178	78	4.1
1.1/2" [40]	38	120	208	88.5	6
2" [50]	50	140	215	88.5	7.3
2.1/2" [65]	63.5	185.5	247	98	12
3" [80]	76	250	274	112.5	16.8
4" [100]	100	240	322	136.5	30.6

Nominal inner diameter	Standard thread connection	Pressure rating	Face to Face norm	Type coding actuator	Brand actuator	Bore	Material ball	Seat material	Spindle material	Article
1/4" [8]	ISO 228-1	1000 PSI WOG	Manufacturer standard	DA20	ECON	Full bore	1.4408	PTFE	1.4401	12533502
3/8" [10]	ISO 228-1	1000 PSI WOG	Manufacturer standard	DA20	ECON	Full bore	1.4408	PTFE	1.4401	12533503
1/2" [15]	ISO 228-1	1000 PSI WOG	Manufacturer standard	DA20	ECON	Full bore	1.4408	PTFE	1.4401	12533504
3/4" [20]	ISO 228-1	1000 PSI WOG	Manufacturer standard	DA20	ECON	Full bore	1.4408	PTFE	1.4401	12533505
1" [25]	ISO 228-1	1000 PSI WOG	Manufacturer standard	DA20	ECON	Full bore	1.4408	PTFE	1.4401	12533506
1.1/4" [32]	ISO 228-1	1000 PSI WOG	Manufacturer standard	DA40	ECON	Full bore	1.4408	PTFE	1.4401	12533507
1.1/2" [40]	ISO 228-1	1000 PSI WOG	Manufacturer standard	DA80	ECON	Full bore	1.4408	PTFE	1.4401	12533508
2" [50]	ISO 228-1	1000 PSI WOG	Manufacturer standard	DA80	ECON	Full bore	1.4408	PTFE	1.4401	12533509
2.1/2" [65]	ISO 228-1	1000 PSI WOG	Manufacturer standard	DA130	ECON	Full bore	1.4408	PTFE	1.4401	12533510
3" [80]	ISO 228-1	1000 PSI WOG	Manufacturer standard	DA200	ECON	Full bore	1.4408	PTFE	1.4401	12533511
4" [100]	ISO 228-1	1000 PSI WOG	Manufacturer standard	DA300	ECON	Full bore	1.4408	PTFE	1.4401	12533512

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.