



JC Ball valve Series: 41501RIICG Type: 3327 Stainless steel Fire safe Internal thread (NPT) Class 1500


Characteristics

Series: 41501RIICG
Type: 3327
Norm: ASME
Construction type: 2-way
Housing construction: 1-part
Housing material: Stainless steel
Material quality: 1.4404
Connection: Internal thread (NPT)
Secondary spindle seal material: FPM (FKM)
Tertiary spindle seal material: Graphite

Body seal: Graphite
Actuator material: Ductile cast iron
Minimum medium temperature (continuous): -50 °C
Maximum medium temperature (continuous): 260 °C
Fire safe: Yes

Application

- Recommended in: Chemical



Nominal inner diameter	Standard thread connection	Pressure rating	Face to Face norm	Manual operation	Bore	Material ball	Seat material	Spindle material	Primary spindle seal material	Article
1/2" [15]	ASME B1.20.1	Class 1500	Manufacturer standard	Handle	Full bore	ASTM A351 CF8M	RPTFE	1.4006	RPTFE	11604305
3/4" [20]	ASME B1.20.1	Class 1500	Manufacturer standard	Handle	Full bore	ASTM A351 CF8M	RPTFE	1.4006	RPTFE	11604307
1" [25]	ASME B1.20.1	Class 1500	Manufacturer standard	Handle	Full bore	ASTM A351 CF8M	RPTFE	1.4006	RPTFE	11604308
1.1/2" [40]	ASME B1.20.1	Class 1500	Manufacturer standard	Handle	Full bore	ASTM A351 CF8M	RPTFE	1.4006	RPTFE	11604309

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.