

ASAHI Ball valve Series: 21 Type: 3732 PVC-U Flange PN10/16



Characteristics

Series: 21
Type: 3732
Construction type: 2-way
Housing construction: 3-part
Housing material: PVC-U
Connection: Flange
Spindle material: PVC-U
Primary spindle seal material: EPDM
Secondary spindle seal material: EPDM
Body seal: EPDM


Actuator material: ABS

Minimum medium temperature (continuous): 0 °C

Maximum medium temperature (continuous): 60 °C

Application

- Recommended in: Chemical



Size table:

DN	d mm	L mm	H mm	M mm	A mm	Weight kg
DN10	13	120	43.5	80	90	0.3
DN15	15	130	51.5	92	95	0.4
DN20	20	150	59.5	100	105	0.6
DN25	25	160	68	110	115	0.8
DN32	32	180	80.5	121	140	1.2
DN40	40	200	89	131	150	1.7
DN50	51	230	102.5	159	165	2.5
DN65	65	290	126	200	185	3.3
DN80	78	310	140	240	200	4.9
DN100	100	350	178	300	220	10.5

Nominal inner diameter	External tube diameter of connection mm	Pressure rating	Pressure rating flange	Face to Face norm	Manual operation	Bore	Material ball	Seat material	Kv value m³/h	Article
DN10	16	PN16	PN10	EN 558, Series 1	Handle	Full bore	PVC-U	PTFE	6.6	12478740
DN15	20	PN16	PN10	EN 558, Series 1	Handle	Full bore	PVC-U	PTFE	12	12478741
DN20	25	PN16	PN10	EN 558, Series 1	Handle	Full bore	PVC-U	PTFE	24.9	12478742
DN25	32	PN16	PN10	EN 558, Series 1	Handle	Full bore	PVC-U	PTFE	40.3	12478743
DN32	40	PN16	PN10	EN 558, Series 1	Handle	Full bore	PVC-U	PTFE	62.4	12478744
DN40	50	PN16	PN10	EN 558, Series 1	Handle	Full bore	PVC-U	PTFE	125.7	12478745
DN50	63	PN16	PN10	EN 558, Series 1	Handle	Full bore	PVC-U	PTFE	156.9	12478746
DN65	75	PN16	PN10	EN 558, Series 1	Handle	Full bore	PVC-U	PTFE	320	12478747
DN80	90	PN16	PN10	EN 558, Series 1	Handle	Full bore	PVC-U	PTFE	430	12478748
DN100	110	PN10		EN 558, Series 1	Handle	Full bore	PVC-U	PTFE	720	12478750

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.