



BLICKLE Castor wheel series BH-ALTH, BK-ALTH

Pressed steel fixed castor, heavy duty brackets, with top plate fitting, Heavy duty wheel with Blickle Extrathane® polyurethane tread, with aluminium wheel centreBracket: Made of pressed steel. Bolted wheel axle. Zinc-plated, blue-passivated, Cr6-free. Wheels: Tyre & running tread: Made of high-quality polyurethane-elastomer Blickle Extrathane®. Color: light brown, Shore: 92° Shore AHigh chemical resistance to many aggressive substances. Operating temperature: -25° C to +70° C, temporarily up to +90° C. At ambient temperatures above +40° C the load capacity is reduced. The indicated load capacity refers to applications without obstacles. Maintenance-free under standard conditions.

Characteristics

Series: BH-ALTH

Type: BH-ALTH 200K

Wheel model	Tread material	Diameter	Width	Bearing weight	Bearing	Temperature range	Article
		mm	mm	kg		°C	
Rigid caster	PUR (Polyurethane)	80	30	180	Ball bearing	-25 / 70	11078711
Rigid caster	PUR (Polyurethane)	100	40	250	Ball bearing	-25 / 70	10067125
Rigid caster	PUR (Polyurethane)	100	40	250	Ball bearing	-25 / 70	11158285
Rigid caster	PUR (Polyurethane)	125	40	350	Ball bearing	-25 / 70	12533989
Rigid caster	PUR (Polyurethane)	125	40	350	Ball bearing	-25 / 70	11091597
Rigid caster	PUR (Polyurethane)	125	40	350	Ball bearing	-25 / 70	11156091
Rigid caster	PUR (Polyurethane)	125	40	350	Ball bearing	-25 / 70	11176616
Rigid caster	PUR (Polyurethane)	150	50	500	Ball bearing	-25 / 70	12533992
Rigid caster	PUR (Polyurethane)	160	50	550	Ball bearing	-25 / 70	11235247
Rigid caster	PUR (Polyurethane)	180	50	600	Ball bearing	-25 / 70	12533995
Rigid caster	PUR (Polyurethane)	200	50	800	Ball bearing	-25 / 70	11132738

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.