



BLICKLE Castor wheel series BH-SE, BK-SE

Pressed steel fixed castor, heavy duty brackets, with top plate fitting, Heavy duty wheel with elastic solid rubber tyres 'Blickle EasyRoll', with nylon wheel centreBracket: Made of pressed steel. Bolted wheel axle. Zinc-plated, blue-passivated, Cr6-free.Wheels: Tyre & running tread: Made of high-quality elastic solid rubber in smooth rolling quality "Blickle EasyRoll". Color: black, Shore: 65° Shore AChemical resistance to many aggressive substances, except oils. Operating temperature: -25° C to +80° C, temporarily up to +100° C. At ambient temperatures above +60° C the load capacity is reduced.

Characteristics

Series: BH-SE

Type: BK-SE 80K

Wheel model	Tread material	Diameter	Width	Bearing weight	Bearing	Temperature range	Article
		mm	mm	kg		°C	
Rigid caster	Solid rubber	80	45	200	Ball bearing	-25 / 80	12534800
Rigid caster	Solid rubber	80	45	200	Ball bearing	-25 / 80	12534322
Rigid caster	Solid rubber	100	45	270	Ball bearing	-25 / 80	11214285
Rigid caster	Solid rubber	160	50	450	Ball bearing	-25 / 80	12534317
Rigid caster	Solid rubber	200	50	600	Ball bearing	-25 / 80	12534319
Rigid caster	Solid rubber	250	60	850	Ball bearing	-25 / 80	12534321

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.