



BLICKLE Castor wheel series B-POTH, BH-POTH

Pressed steel fixed castor, medium duty brackets, with top plate fitting, Wheel with thermoplastic polyurethane tread, with heavy nylon wheel centre, non-marking, non-staining Bracket: Made of pressed steel. Bolted wheel axle. Zinc-plated, blue-passivated, Cr6-free. Wheels: Tyre & running tread: Made of high-quality thermoplastic polyurethane. Color: dark grey, Shore: 94° Shore A Very high chemical resistance to many aggressive substances. Operating temperature: -25° C to +70° C, temporarily up to +90° C. At ambient temperatures above +35° C the load capacity is reduced. Maintenance-free under standard conditions.

Characteristics

Series: B-POTH
Type: B-POTH 160K

Wheel model	Tread material	Diameter	Width	Bearing weight	Bearing	Temperature range	Article
		mm	mm	kg		°C	
Rigid caster	Polyamide 6	125	40	200	Slide bearing	-25 / 70	12535238
Rigid caster	Polyamide 6	160	45	400	Ball bearing	-25 / 70	12535251
Rigid caster	PUR (Polyurethane)	100	35	200	Ball bearing	-25 / 70	11542778
Rigid caster	PUR (Polyurethane)	100	35	200	Needle roller bearing	-25 / 70	11063208
Rigid caster	PUR (Polyurethane)	100	35	200	Slide bearing	-25 / 70	12535233
Rigid caster	PUR (Polyurethane)	150	45	400	Slide bearing	-25 / 70	12535242
Rigid caster	PUR (Polyurethane)	160	45	400	Needle roller bearing	-25 / 70	12535252

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.