



BLICKLE Castor wheel series B-V, BH-V

Pressed steel fixed castor, medium duty brackets, with top plate fitting, Wheel with standard solid rubber tyres, with pressed steel rim, reinforced design
Bracket: Made of pressed steel. Bolted wheel axle. Zinc-plated, blue-passivated, Cr6-free.
Wheels: Tyre & running tread: Made of standard solid rubber. Color: black, Shore: 80° Shore A
Chemical resistance to many aggressive substances, except oils. Operating temperature: -25° C to +80° C, temporarily up to +100° C. At ambient temperatures above +60° C the load capacity is reduced.

Characteristics

Series: B-V

Type: B-V 100R

Wheel model	Tread material	Diameter	Width	Bearing weight	Bearing	Temperature range	Article
		mm	mm	kg		°C	
Rigid caster	Solid rubber	80	25	50	Needle roller bearing	-25 / 80	10016369
Rigid caster	Solid rubber	100	30	70	Needle roller bearing	-25 / 80	10016370
Rigid caster	Solid rubber	100	30	70	Needle roller bearing	-25 / 80	11240415
Rigid caster	Solid rubber	125	37.5	100	Needle roller bearing	-25 / 80	10016371
Rigid caster	Solid rubber	125	37.5	100	Needle roller bearing	-25 / 80	12535677
Rigid caster	Solid rubber	140	37.5	115	Needle roller bearing	-25 / 80	10016372
Rigid caster	Solid rubber	160	40	135	Needle roller bearing	-25 / 80	10016373
Rigid caster	Solid rubber	180	50	170	Needle roller bearing	-25 / 80	11069904
Rigid caster	Solid rubber	200	50	205	Ball bearing	-25 / 80	12535695
Rigid caster	Solid rubber	200	50	205	Needle roller bearing	-25 / 80	10016374
Rigid caster	Solid rubber	250	60	295	Needle roller bearing	-25 / 80	12535708
Rigid caster	Solid rubber	280	70	385	Needle roller bearing	-25 / 80	12535715