

SAUNDERS Diaphragm valve Series: A Type: 3049 Ductile cast iron Without lining Internal thread (BSPP) PN10/16

Characteristics

Series: A **Type:** 3049 Norm: EN (DIN)

Housing construction: A [Weir type] Housing material: Ductile cast iron

Material quality: EN-JS1040

Surface protection: Manufacturer standard **Connection:** Internal thread (BSPP)

Standard thread connection: ISO 228-1

Face to Face norm: Manufacturer standard Manual operation: Hand wheel, rising with rising

With position indicator: No

Application

• Recommended in: Chemical, Utilities

Material body lining	Membrane material	Material code diaphragm	Nominal inner diameter	Pressure rating	Face to Face length mm	Material bonnet	Actuator material		Maximum medium temperature (continuous) °C	Article
Without lining	EPDM	XE	1/4" [8]	PN16	49	Aluminium	ABS	-10	130	11234059
Without lining	EPDM	XE	3/8" (10)	PN16	49	Aluminium	ABS	-10	130	11320406
Without lining	NBR	С	1/4" [8]	PN16	49	Aluminium	ABS	-10	100	10051831
Without lining	NBR	С	3/8" (10)	PN16	49	Aluminium	ABS	-10	100	10051833
Without lining	PTFE/EPDM	PE	3/8" (10)	PN10	49	Aluminium	ABS	-10	150	13035124

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

E-mail: appendages@eriks.nl



Page 1/1

PR_EC011426_0008_EN_26.04.2024